ESOF028-ECA Series

Outdoor Cabinet



There are lots of external forces can threaten the outdoor system, not only the temperature but also the humidity. Then the cooling function plays an important role in the power system, and the flexibility is also the common requirement to apply several kinds of electronics. ESOF028-ECA Series is developed for that.

Beside well protected by robust enclosure with IP55 class, the internal configuration can be adjusted easily, such as the numbers of wall layers, the type of thermal systems.

To keep the sensitive modules, batteries functioning in a high level and to reduce the CAPEX and OPEX, ESOF028-ECA Series is the ideal solution for the challenges. Your concern, our mission.

Key Features

- -48V_{DC} output for telecommunication applications
- Air-con, Fan and TEC cooling
- IP55 protection class for outdoor application
- Perfectly integrated with Delta
 Telecom Power system controller

Applications

- •3G / 4G / 5G
- Fixed Line
- Datacom



ESOF028-ECA Series



AC INPUT

GOAQCM-00-ZL

Voltage (nominal)	Single phase, 4W (L1, L2, N, FG); 100 - 120V _{AC,} 12A (Max.)
Frequency	50/60Hz
DC INPUT	
Voltage (nominal)	 54V_{DC}, 39A (Max.) 54V_{DC}, 46A (Max.)
MECHANICAL	
Dimensions (W x H x D)	856.8 x 2132.8 x 1156.1mm (33.7 x 84.0 x 45.5in)
Weight	approx. 215.5kg (475lb) (empty enclosure)
ENVIRONMENTAL	
Operating Temperature	0°C to +46°C (32°F to +115°F)
Storage Temperature	-40°C to +70°C (-40°F to +158°F)
Altitude	0 to +4000m
Related Humidity	95%, non-condensing (Max.)
Acoustic Noise	55dBA
Cooling	 Power room: EX-E08 C (Air-con and Fan) EX-E08 D (Air-con) Battery room: TEC x2
STANDARDS	
Environment	RoHS

Delta Electronics Inc.

3 Tungyuan Road, Chungli Industrial Zone, Taoyuan City 32063, Taiwan.
T +886 3 452 6107 / F +886 3 452 7314
www.deltaww.com

 $\ensuremath{^\star}$ All specifications are subject to change without prior notice.

